



## FEATURES

Alimentatore GF850 EVO - 850W, 80Plus Gold, Ventola FDB 12cm, Cond Giapponesi, Modulare

## SPECIFICATIONS

|                   |   |
|-------------------|---|
| Power             | 850W  |
| Version           | ATX V2.31   |
| Certification     | 80Plus® Gold  |
| PFC               | Active  |
| Circuit           | DC to DC  |
| Input voltage     | 100-240Vac  |
| Efficiency        | Load Efficiency<br>20% 87%<br>50% 90%<br>100% 87%   |
| CE EMI compliance | Yes   |
| Compliance        | ErP Lot 6   |
| It supports       | ATX12V V2.3 and backwards compatible  |
| ERP               | <0.5W   |
| MTBF              | 100000 hours  |
| Protections       | Over current, short circuit, electric shock, over power, over voltage and under voltage for the safety of critical system components (OVP, SCP, OPP, OVP, UVP, SIP) |
| On / off switch   | Yes   |
| Connectors        | 24Pin;<br>3x Molex 4Pin;<br>MOBO 4 + 4Pin,<br>2x (6 + 2) + (6 + 2) Pin,<br>9xSATA   |

Type of cables  
Cable length

Fully modular black flat  
1x24P 570MM (modular cable)  
1x (4P + 4P) 670MM (modular cable)  
1x (6 + 2/6 + 2) Pin 530 + 150MM (modular cable)  
2x 3SATA 530 + 150 + 150MM (modular cable)  
1x (3IDE + 1SATA) 530 + 150 + 150 + 150MM (modular cable)  
100% Japanese 105c  
120mm FDB "Fluid Dynamic Bearing" silent with thermal control  
Rough black anti scratch  
Single rail  
1878\*145.7\*86mm  
2.53Kg (3.05Kg with box)

Capacitors  
Fan

Chassis  
12v

Dimensions  
Weight

## PACKING INFORMATION

Code: **ITPSEGF850**  
EAN: **8056157881056**  
Warranty: **60 months**

## SOCIAL MEDIA COMMUNICATION

