



FEATURES

Alimentatore GF1000 EVO - 1000W, 80Plus Gold, Ventola FDB 12cm, Cond Giapponesi, Modulare

SPECIFICATIONS

Power	1000W
Version	ATX V2.31
Certification	80Plus® Gold
PFC	Active
Circuit	DC to DC
Input voltage	100-240Vac
Efficiency	Load Efficiency 20% 87% 50% 90% 100% 87%
CE EMI compliance	Yes
Compliance	ErP Lot 6
It supports	ATX12V V2.3 and backwards compatible
ERP	<0.5W
MTBF	100000 hours
Protections	Over current, short circuit, electric shock, over power, over voltage and under voltage for the safety of critical system components (OVP, SCP, OPP, OVP, UVP, SIP)
On / off switch	Yes
Connectors	24Pin; 3x Molex 4Pin; MOBO 4 + 4Pin, 2x (6 + 2) + (6 + 2) Pin, 9xSATA

Type of cables
Cable length

Fully modular black flat
1x24P 570MM (modular cable)
2x (4P + 4P) 670MM (modular cable)
1x (6 + 2/6 + 2) Pin 530 + 150MM (modular cable)
2x 3SATA 530 + 150 + 150MM (modular cable)
1x (3IDE + 1SATA) 530 + 150 + 150 + 150MM (modular cable)
100% Japanese 105c
120mm FDB "Fluid Dynamic Bearing" silent with thermal control
Rough black anti scratch
Single rail
1878*145.7*86mm
2.7Kg (3.1Kg with box)

Capacitors
Fan

Chassis
12v

Dimensions
Weight

PACKING INFORMATION

Code: **ITPSEGF1000**
EAN: **8056157881759**
Warranty: **60 months**

SOCIAL MEDIA COMMUNICATION

