

FD 2588 – Two Dimensional Scanner



Product Features
Quickly identify the screen 1D/2D code
No plugins, lightning billing
Application scenario is rich
Appearance with ergonomic design
Stable, precise, convenient, practical and efficient
Compatible with a variety of systems

Application scenarios: supermarket/convenience store cashiers, customer service desk, ticket ticketing windows, O2O application sites.

Detailed Parameters	
Performance	Imagine Sensor: 640×480 CMOS Ambient Light Intensity: 0~100000 Lux

Symbologies	<p>1D: Code 128, UCC/EAN-128, AIM 12, EAN-8, EAN-13, ISSN, ISBN, UPC-E, UPC-A, Interleaved 2 of 5, ITF-6, ITF-14, Matrix 2 of 5(European Matrix 2 of 5), Industrial 25, Standard 25, Code 39, Codabar, Code 93, Code 11, Plessey, MSI-Plessey, RSS-14, RSS-Limited, RSS-Expand</p> <p>2D: PDF417, Data Matrix, QR, Micro QR</p>
Resolution	≥5mil
Typical Depth of Field	QR CODE(30MIL) 0-15CM CODE 128 (10MIL) 0-18CM
Scan Angle	<p>Pitch: ±60°@ 0°Roll and 0° Skew</p> <p>Roll: 360°@ 0°Pitch and 0° Skew</p> <p>Skew: ±55°@ 0°Roll and 0° Pitch</p>
Symbol Contrast	≥30%
Interface	RS-232, USB
Physical	<p>Dimensions:163*65*91mm (L*W*H)</p> <p>Weight: USB:188.5g RS232:214.4g</p>
Package	<p>Information: 20 pieces per case, weight 6.8KG</p> <p>Packing Box Size: 463*220*440mm</p> <p>Box Size: 105*90*210mm</p> <p>Bracket (Optional): 20 per case, weight 4.8KG</p>
Notification	Beep, LED indicator
Current	<p>Maximum: <180mA</p> <p>Operating: 150mA±15mA</p> <p>Standby: 120mA±2mA</p>
Environmental	<p>Operating Temperature: -20°C~50°C</p> <p>Storage Temperature: -40°C~70°C</p> <p>Humidity: 5%~95% (non-condensing)</p>

Specifications are subject to change without notice.