



FEATURES

Alimentatore BS750 EVO - 750W, 80Plus Bronze, PFC Attivo, Ventola HDB 12cm, Semi Modulare

SPECIFICATIONS

Power	750W
Version	ATX V2.31
Certification	80Plus® Bronze
PFC	Active
Input voltage	100-240Vac
Efficiency	Load Efficiency 20% 82% 50% 85% 100% 82%
CE EMI compliance	Yes
Compliance	ErP Lot 6
It supports	ATX12V V2.3 and backwards compatible
ERP	<0.5W
MTBF	100000 hours
Protections	Over current, short circuit, electric shock, over power, over voltage and under voltage for the safety of critical system components (OVP, SCP, OPP, OVP, UVP, SIP)
On / off switch	Yes
Connectors	24Pin; 3x Molex 4Pin; MOBO 4 + 4Pin, (6 + 2) + (6 + 2) Pin, 7xSATA
Type of cables	Semi modular black flat

Cable length (from PCB)

Alimentation cable

Capacitors

Fan

Chassis

12v

Dimensions

Weight

1x24P	700MM
1x (4P + 4P)	800MM
1x (6 + 2/6 + 2) Pin	550 + 150MM (modular cable)
2x 3SATA	550 + 150 + 150MM (modular cable)
1x (3IDE + 1SATA)	550 + 150 + 150 + 150MM (modular cable)
	1,5m included
	Taiwanese TEAPO 105c
	120mm silent hydraulic bearing with thermal control
	Rough black anti scratch
	Single rail
	160 * 150 * 86mm
	2.24Kg (2.7Kg with box)

PACKING INFORMATION

Code: ITPSEBS750
EAN: 8056157881025
Warranty: 36 months

SOCIAL MEDIA COMMUNICATION

